



Product Data Sheet

Product Description: BinCoat is a direct to metal formulated coating. The product contains anti-flash and long term rust inhibitors. Formulated with Alkyd and water based resins known as a “hybrid” formula for long life durability in exterior applications. Available in flat, eggshell and semi-gloss sheens. Stock colors; white, gray, tan, red and black. Custom colors are available in 50 gallon minimum batches.

Quality Control: Our paints are rigorously tested for viscosity, adhesion, coverage, hide and pH. Before packaging we add preservatives and filter for a consistent high quality, smooth and clean product.

Drying Time: To touch 45 - 90 minutes depending on temperature and humidity. Good ventilation will decrease drying time.

Thinning: Use at supplied consistency. If thinning is required use water not to exceed a half pint per gallon.

Clean up: Use warm soapy water for hands and tools.

Coverage: 300 to 350 sq. Ft./gal. on smooth surfaces.

Surface Preparation: All surfaces must be free of dirt, oil, soot, loose and peeling paint. Rusty areas should be wire brushed, dust removed and primed for best results.

Application: Apply at temperatures above 50 degrees F. but not in extreme heat. Stir thoroughly before use. May be brushed, rolled or sprayed. Do not apply when rain, mist or fog may damage fresh paint film.



Composition/Properties:

Titanium Dioxide: 10-15%	Resin: 20-40%
Fillers/Extenders: 40-45%	Additives: 5-10%
VOC < 250 g/L	Viscosity: 90 - 100 KU
Gloss: 1 - 45%	Density: 1.2 - 1.4

Non Hazardous, water based paint.

Safety Precautions: Avoid breathing both vapors and mist during the application process. Avoid contact with eyes and skin. Wash thoroughly after handling this product. Refer to Material Safety Data Sheet for more detailed health and safety tips and recommended storage, transportation and disposal guidelines. In case of spill or uncontrolled release, absorb with inert material and dispose of according to local, state and federal codes.

rev 11/1/12

Manufactured by:

