



Product Specifications for Egduls Asphalt Sealer

Product Description: Egduls is a low cost, easy to apply asphalt sealer made from post-manufactured by-products and post-consumer latex paints. This will extend the beauty and life of all asphalt surfaces. This product is an asphalt sealer, but does not contain any petrochemical products.

Surface Preparation: Remove all dirt and loose debris. Cracks larger than 1/4" should be filled with asphalt patch. Oil stains should be removed by a commercial cleaner. Surface should be dry to the touch and as clean as possible.

Application: Mix thoroughly before using. Use squeegee or roller. For best results, use two thin layers rather than one thick application. Wait 24 hours between applications. Use at temperatures above 50 degrees F. with no rain for 48 hours.


Drying Time: To touch 30 - 60 minutes depending on temperature and humidity. Wait at least 24 hours prior to driving on.

Thinning: Use at can consistency. Thinning is not recommended.

Clean up: Use warm soapy water.

Coverage: 40 to 60 sq. ft./gal. on badly cracked surfaces. 70-100 sq. ft./gal. on newer surfaces.

Composition: Titanium Dioxide 10-15%
Fillers/Extenders 40-45% Resin 20-40%
Additives 5-10% VOC < 250 g/L



Rev. 7/09



Remember: By using recycled products you can do your share in utilizing otherwise wasted resources.

Safety Precautions: Avoid breathing both vapors and mist during the application process. Avoid contact with eyes and skin. Wash thoroughly after handling this product. Refer to Material Safety Data Sheet for more detailed health and safety tips.

Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. storage, transportation and disposal guidelines. In case of spill or uncontrolled release, absorb with inert material and dispose of according to local, state and federal codes.