



Product Specifications for Life Cycle[®] Latex Paint

Product Description: All Acrylatex paints are made from post-manufactured by products and post consumer latex paints. These flat latex paints are designed for interior/exterior use.

Drying Time: To touch 30 - 60 minutes depending on temperature and humidity. Good ventilation will decrease drying time.

Thinning: Use at can consistency. If thinning is required use water not to exceed a half pint per gallon.

Clean up: Use warm soapy water for hands and tools.

Coverage: 300 to 350 sq. Ft./gal. on smooth surfaces.

Surface Preparation: All surfaces must be free of dirt, oil, soot, loose and peeling paint. Remove all wallpaper and all glue before painting. Patched holes should be sanded smooth and primed first.

Application: Apply at temperatures above 50 degrees F. but not in extreme heat. Stir thoroughly before use. May be brushed, rolled or sprayed. Do not apply when rain, mist or fog may damage fresh paint film.

Mildew: Do not paint over mildew. Mildew is a fungus, brown, black, gray or white in color and will grow through any coating applied over it. A solution of 50% bleach and water will kill most mildew. Use caution, read bleach label before using.



Remember: By using recycled products you can do your share in utilizing otherwise wasted resources. For interior/exterior applications.

Composition: Titanium Dioxide 10-15%
Fillers/Extenders 40-45% Resin 20-40%
Additives 5-10% VOC < 250 g/L

Safety Precautions: Avoid breathing both vapors and mist during the application process. Avoid contact with eyes and skin. Wash thoroughly after handling this product. Refer to Material Safety Data Sheet for more detailed health and safety tips and recommended storage, transportation and disposal guidelines. In case of spill or uncontrolled release, absorb with inert material and dispose of according to local, state and federal codes.

Rev. 6/13/10